



## KART GRAND PRIX 2T

**Special 23,000 rpm GO Kart Lubricant  
Premix Racing 2 Stroke Engines  
100% Synthetic - Ester**

### TYPE OF USE

Formula specially developed for racing GO KARTS.  
Suitable for all kinds of gasoline fuels, leaded or unleaded, biofuels.  
Racing premix 2 Stroke engines running at very high RPM:  
ROTAX, ATK, PARILLA, PCR, YAMAHA, Ital System, TM, ...

### PERFORMANCES

STANDARDS                      API TC  
   FIA - CIK approval

The specific 100% Synthetic - Esters formulation provides very high lubricating power which decreases friction and reduces wear.  
Keeps engines always perfectly lubricated in extreme use conditions (23,000 rpm / high temperatures).  
Prevents piston rings sticking.  
Keeps engine clean contrary to 2 Stroke conventional racing oils.

### RECOMMENDATIONS

Mixing ratio:  
100 cc: 6%  
125 cc: 4%  
To be adjusted according to your own use and to your tuner's recommendations

### PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.916

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - [www.motul.com](http://www.motul.com)

[motul.com](http://motul.com)

02/21



## KART GRAND PRIX 2T

**Special 23,000 rpm GO Kart Lubricant  
Premix Racing 2 Stroke Engines  
100% Synthetic - Ester**

Viscosity at 40°C (104°F)	ASTM D445	135.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	16.9 mm²/s
Viscosity Index	ASTM D2270	136.0
Pour point	ASTM D97	-33.0 °C / -27.4 °F
Flash point	ASTM D92	256.0 °C / 492.8 °F