

ATF VI

Low viscosity fluid for automatic transmission with slip lockup clutch
Transfer case and Power steering
100% Synthetic

TYPE OF USE

100% Synthetic High performance low viscosity lubricant specially engineered for modern automatic transmission (manual mode, sequential mode, electronically controlled ...) with or without slip lockup clutch requiring a DEXRON VI fluid. Particularly recommended for use in automatic gearboxes, transfer case and power steering systems of American car makers GM, FORD, CHRYSLER,... Asian car makers HONDA, HYUNDAI, KIA, ISUZU, MERCEDES, MITSUBISHI, NISSAN, TOYOTA,... or European car makers FORD, OPEL, ...

Also suitable for use in older automatic gearboxes, torque converters, power steering, mechanical and hydraulic systems where DEXRON III H or DEXRON II D fluids are required.

Before use always refer to the owner manual or handbook of the vehicle.

PERFORMANCES

MOTUL ATF VI is a 100% Synthetic high tech lubricant featuring outstanding low viscosity performance with regards to DEXRON III and MERCON standards requirements.

Thanks to its exclusive and dedicated formula, MOTUL ATF VI:

- Allows Fuel Economy for cars fitted with automatic gearboxes by reducing friction.
- Improves automatic gearboxes reaction at cold temperature.
- Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag.
- Provides anti-shudder performance to avoid vibrations on engine fly wheel.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Extends life time duration, better shear stability at hot temperature and oxidation resistance.
- Anti-wear, anti-corrosion, anti-foam.

RECOMMENDATIONS

Can be mixed only with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Before use always refer to the owner manual or handbook of the vehicle.



ATF VI

Low viscosity fluid for automatic transmission with slip lockup clutch
Transfer case and Power steering
100% Synthetic

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.843
Viscosity at 40°C (104°F)	ASTM D445	30.5 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	6.1 mm²/s
Viscosity Index	ASTM D2270	152.0
Flash point	ASTM D92	217.0 °C / 423.0 °F

Low viscosity fluid for automatic transmission with slip lockup clutch
Transfer case and Power steering
100% Synthetic

OE PERFORMANCES	
ACURA	##08200-9008A, ##08200-9009A, ##08266-99964, #atf, 082000-9001, 08200-9008A, 08200-9009A, 08266-99964, ATF DW-1 (except CVTs), ATF Z1 (except CVTs)
ALLISON TRANS-MISSION	C-4
AUDI	G 055 005, G 055 162, G 055 540, G 060 162
BENTLEY	PY112995PA
BMW	##83220142516, ##83222152426, 83 22 0 142 516, 83 22 0 397 114, 83 22 0 403 248, 83 22 0 403 249, 83 22 0 432 807, 83 22 2 152 426, 83 22 9 400 275, 83 22 9 407 738, 83 22 9 407 858, 83 22 9 407 859, ATF 3+, L12108
CHRYSLER	##68157995AA, ##68157995AB, ##68218057CA, ##68218058CA, ##68218054CA, ##68218925AA, ##68171869AA, 68043742AB, 68157995AA, 68157995AB, 68171866AA, 68171869AA, 68218054CA, 68218057CA, 68218058CA, 68218925AA, ATF+3, ATF+4, DEXRON®-VI Automatic Transmission Fluid, MS 9602, SP IV Automatic Transmission Fluid
CITROËN	RP 9734 R7 for EAT6 transmissions
DAIMLER	##68157995AA, ##68157995AB, ##68218057CA, ##68218058CA, ##68218054CA, ##68218925AA, ##68171869AA, 68043742AB, 68157995AA, 68157995AB, 68171866AA, 68171869AA, 68218054CA, 68218057CA, 68218058CA, 68218925AA, ATF+3, ATF+4, DEXRON®-VI Automatic Transmission Fluid, MS 9602, SP IV Automatic Transmission Fluid
DS (CAPSA)	RP 9734 R7 for EAT6 transmissions
FORD	MERCON LV, XT-10-QLVC
GENERAL MOTORS	##9986153, ##88861003, ##88861004, ##9986333, ##GMW16444, 88861003, 88861004, 9986153, 9986333, GM 1940184, GM 93165414, GM DEXRON HP ATF, GM DEXRON II D, GM DEXRON III H, GM DEXRON VI, GMW16444
HONDA	##082000-9001, ##08266-9904, ##08266-99907, 082000-9001, 08200-9005, 08200-9017, 08266-9904, 08266-99907, ATF-11, ATF DW-1 (except CVTs), ATF-TYPE 3.1, ATF Z1 (except CVTs), B2618-OLE-025
HYUNDAI	##040000C90SG, ##00232-1904/04500-00115, 00232-1904, 040000C90SG, 04500-00115, SP-IV, SP-IV M, SP-IV-RR
INFINITI	MATIC D, MATIC J, MATIC K, MATIC S
ISUZU	ATF Z1 (except CVTs)
JAGUAR	##02JDE 26444, 02JDE 26444, Fluid 8432
KIA	SP-IV, SP-IV M, SP-IV-RR
LAND ROVER	LR023288, LR023289, TYK500050
LEXUS	##00289-ATFWS, ##08886-02303, ##08886-02305, ##08886-80803, 00289-ATFWS, 08886-02303,

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

Low viscosity fluid for automatic transmission with slip lockup clutch
Transfer case and Power steering
100% Synthetic

	08886-02305, 08886-80803, ATF Type T-IV, ATF WS, JWS 3324, NWS 9638
MASERATI	##231603, 231603, M-1375.4
MAZDA	##0000-77-122E-01, 0000-77-122E-01, ATF FZ, MERCON LV
MERCEDES-BENZ	A 001 989 45 03, A 001 989 68 03, A 001 989 77 03, A 001 989 78 03, MB 236.12, MB 236.14, MB 236.15 (except FE benefits), MB 236.41
MITSUBISHI	ATF-MA1, ATF SPH-IV, ATF SP-IV, Diamond ATF SP II, MZ320762, SP III
NISSAN	999MP-MTS00P, KLE24-00002, MATIC D, MATIC J, MATIC K, MATIC S
PEUGEOT	RP 9734 R7 for EAT6 transmissions
PORSCHE	##00004330400, 000 043 304 00
SSANGYONG	DSIH 5M-66 Material Specification Rev 3
TOYOTA	##00289-ATFWS, ##08886-02303, ##08886-02305, ##08886-80803, 00289-ATFWS, 08886-02303, 08886-02305, 08886-80803, ATF Type T-IV, ATF WS, JWS 3324, NWS 9638
VW	#g 05, #g 052 025, G 055 005, G 055 162, G 055 540, G 060 162
ZF	M-1375.4, M-1375.5, M-1375.6, S671 090 255, S671 090 281, S671 090 312
PRODUCTS	
AML	##4G4319A509/AA/S, 4G4319A509 / AA / S
FUCHS	ATF 3292, ATF 4400, ATF 6000 SL
JALOS	JASO 1A
PENTOSIN	#fll
PSA Groupe	#lds, RP 9734 R7 for EAT6 transmissions
SHELL	#m, #13, L-12108, M-1375.4, M-1375.5, M-1375.6
ZF	##S671090255, ##S671090281, ##S671090312, Lifeguard 6, Lifeguard 6 Plus, Lifeguard 8, M-1375.4, M-1375.5, M-1375.6, S671 090 255, S671 090 281, S671 090 312, TE-ML 11

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com