

DEXRON IID

Automatic Transmission Fluid
Power steering system
Torque converters and hydraulic systems
Mineral

TYPE OF USE

Automatic Transmission Fluid (ATF) for all systems where DEXRON II standard is required.
 Automatic gearboxes and transmissions, torque converters, power steering systems, hydraulic circuits, boat reversing gears...

PERFORMANCES

PERFORMANCES MAN Type 339 V1, MAN Type 339 Z1, MERCEDES-BENZ MB-Approval 236.7, VOITH 55.6335.32 (G607), ZF TE-ML 11A under N°ZF001104, ZF TE-ML 04D under N°ZF001104, ZF TE-ML 14A under N°ZF001104, ALLISON TRANSMISSION C-4, CATERPILLAR TO-2, GENERAL MOTORS GM DEXRON II D

Very high fluidity at low temperatures which allows easy gear changing.
 Thermal stability under high temperature.
 Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

MOTUL DEXRON II D is the latest evolution from DEXRON specification.
 Can be used each time "DEXRON B" specification is recommended.
 Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.865
Viscosity at 40°C (104°F)	ASTM D445	38.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.8 mm ² /s

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.



DEXRON IID

Automatic Transmission Fluid
Power steering system
Torque converters and hydraulic systems
Mineral

Viscosity Index	ASTM D2270	179.0
Flash point	ASTM D92	224.0 °C / 435.0 °F
Pour point	ASTM D97	-36.0 °C / -33.0 °F