

**Mechanical transmission lubricant  
Extreme Pressure****TYPE OF USE**

All gearboxes, gearbox/differential and hypoid differentials without limited slip system operating under moderate loads and revolution speed or transfer gearboxes, mechanical transmissions without hypoid gear, reduction gears operating under moderate to severe load and revolution speed.

**PERFORMANCES**

STANDARDS	API GL-4 MIL-L -2105
PERFORMANCES	MAN 341 type N, ZF TE-ML 16A

Extreme Pressure lubricant for an efficient anti-wear protection.  
Very high lubricating properties to reduce friction.  
Suitable for any type of seal.  
Anti-corrosion, Anti-foam.

**RECOMMENDATIONS**

Oil change: According to manufacturers' requirements and adjust according to your own use.

**PROPERTIES**

Viscosity grade	SAE J 306	90
Density at 20°C (68°F)	ASTM D1298	0.892
Viscosity at 40°C (104°F)	ASTM D445	181.2 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	16.8 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	98.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



## EPL 90

**Mechanical transmission lubricant  
Extreme Pressure**

Pour point	ASTM D97	-15.0 °C / 5.0 °F
Flash point	ASTM D92	222.0 °C / 431.0 °F